



# GatorSeal®

GRANULAR SURFACE SELF-ADHERED UNDERLAYMENT



WEATHER  
RESISTANT



EASY  
INSTALLATION



3 months

UNCOVERED  
EXPOSURE



20  
YEAR  
LIMITED  
WARRANTY

- Modified asphalt reinforced with an extra heavy fiberglass mat
- Uniformly seals to the deck and around fastener penetrations
- UV protected surface
- Helps to protect building from damage due to ice dams and wind driven rain
- Aggressive bond at low temperatures

# Features and Benefits



WEATHER RESISTANT

## Durable Protection – All Season

An extra heavy fiberglass reinforcement provides strength and durability. The proprietary modified asphalt helps to prevent moisture penetration and damage due to wind, rain, ice and snow. The opaque granules on the surface provide great traction during installation and protect against UV. Sealing direct to the roof deck makes GatorSeal® a good choice for those critical areas of the roof such as valleys, perimeters, eaves, chimneys, walls, dormers and skylights.



UNCOVERED EXPOSURE

## 3 Months Uncovered Exposure

Can be left uncovered and exposed to the elements for up to 90 days without degradation.



EASY INSTALLATION

## Easy Installation

No heat, special tools or equipment are required to install GatorSeal® in cold or warm climates. The self adhesive layer is covered with a release sheet, easily removed during installation to permanently bond to the roof deck or base sheet.



YEAR LIMITED WARRANTY

## Product Performance

20 year limited warranty under shingle, concrete or clay tile roofs. GatorSeal® meets or exceeds all national and Florida building code requirements and consistently outperforms conventional underlayments.



## NEW!

Build a customized truck load for any combination of the following products: Boral TileSeal®, Boral TileSeal® 50, GatorSeal®, Citadel® Plus, StormSentry®. Call Customer Service at 1.800.669.8453 for more information or to build your customized truck load.

### CERTIFICATIONS / APPROVALS

**Florida** FL14317  
**ICC** ESR-1783  
**ASTM** D1970

### PART NUMBERS

**91753** Picku Up at Plant  
**91746** Drop Ship - 660 Rolls

### SPECIFICATIONS

**Roll Size** 3' x 66.6' (200 sq ft)  
**Roll Weight** 70 lbs (nominal)  
**Coverage** 2 squares  
**Thickness** 50 mils (nominal)  
**Rolls per pallet** 20 Rolls  
**Pallet weight** 1450 lbs (nominal)

**NOTE:** This product is not recommended for use on roofs with tiles installed without battens. When loading tiles onto GatorSeal®, make sure the tiles are supported by properly fastened battens to prevent tiles from sliding down the roof slope.



Download a QR Code reader app for your smartphone, then take a photo to visit our website.

