



Boral™ Tile Mortar for Florida

ONE-STEP FIBER-REINFORCED MORTAR FOR TILE ROOF WEATHER BLOCKING



WEATHER
RESISTANT



AESTHETICS



SAVE
TIME & MONEY



EASY
INSTALLATION

Boral™ Tile Mortar is a pre-blended mix of graded natural river sand, portland cement and oxide for color.

- Proprietary formulation reduces potential for efflorescence
- Color added pre-mixed mortar - just add water
- Fiber-reinforced for strength
- Type S Mortar resists shrinkage and cracking
- 10-30 linear feet coverage per bag - varies by profile

Boral™ Tile Mortar for Florida

ONE-STEP FIBER-REINFORCED MORTAR FOR TILE ROOFING



HIGH PERFORMANCE FOR EXTREME WEATHER



WEATHER
RESISTANT

Durable Protection – All Season

Boral™ Tile Mortar is specifically designed for tile roof weather blocking. A mixture of Integral Water Repellent (IWR) is added to reduce water penetration and efflorescence.



EASY
INSTALLATION

Easy Installation

This one-step solution is a pre-blended mix of graded natural river sand, portland cement and oxide for color, requiring just water to be added.



SAVE
TIME & MONEY

Save Time and Money

Each 80 Lb bag yields 10-30 linear feet depending on tile profile. Highly workable - saves time and reduces labor. Available as single bags, pallets and full truck load. Highly workable, saves time and reduces labor.



AESTHETICS

Available in Multiple Colors

Boral™ Tile Mortar is uniformly blended to ensure consistency of color at all hips, ridges, gables, and valleys making any tile roof aesthetically pleasing. Broad color offering to help seamlessly match almost any roof tile.

**BORAL™ TILE MORTAR IS NOT FOR USE TO ATTACH ROOF TILES.
FOR WEATHER BLOCKING ONLY.**



EXCELLENT BOND - REPELS WATER

- Formulated for superior performance, consistency of color, bonding strength and is repellent to water
- Boral™ Tile Mortar is considered a Type S mortar that is engineered to minimize shrinkage and cracking
- Our Mortar includes ¼" polymer fibers that increase bonding strength
- By using Boral's proprietary admixture, the designer, property owner and contractor are assured of the best possible long term results



EFFLORESCENCE STATEMENT

Efflorescence is a temporary surface condition common to concrete products caused by the chemical nature of cement. It is superficial and in no way affects the quality or functional properties of Boral™ Tile Mortar. Sealers are generally not necessary on Boral™ Tile Mortar. However, if a sealer is used, please contact the manufacturer of the sealer for information regarding actual performance and application instructions.

CERTIFICATIONS / APPROVALS

ASTM C-270

SPECIFICATIONS

Packaging	80 Lb Bag
Bags Per Pallet	42 Bags
Pallets Per Truck	14 Pallets
Bags Per Truck	588 Bags

HANDLING AND STORAGE

Boral™ Tile Mortar may be stored 3 pallets high provided a slip sheet of 3/8" minimum thickness of plywood is provided between pallets. Bags are to be stored in a clean, dry, cool area. Do not store directly in sunlight without proper protection.

COLOR OFFERING

Description	Part Numbers		Color Sample
	Single Bag	Mixed Truck Load	
Boral™ Tile Mortar Casa Grande	9MOR6169	9MOR6169DSMTL	
Boral™ Tile Mortar Charcoal	9MOR1430	9MOR1430DSMTL	
Boral™ Tile Mortar Chestnut Burnt	9MOR3242	9MOR3242DSMTL	
Boral™ Tile Mortar Dark Bordeaux	9MOR7944	9MOR7944DSMTL	
Boral™ Tile Mortar Desert Sage	9MOR0024	9MOR0024DSMTL	
Boral™ Tile Mortar Marbled Canyon Red	9MOR7378	9MOR7378DSMTL	
Boral™ Tile Mortar Red	9MOR7027	9MOR7027DSMTL	
Boral™ Tile Mortar Sandstorm	9MOR0026	9MOR0026DSMTL	
Boral™ Tile Mortar Terra Cotta	9MOR6100	9MOR6100DSMTL	

NOTE: Color samples shown may vary from actual colors. Drop ship full and mixed truck loads are only available in the contiguous United States.



Download a QR Code reader app for your smartphone, then take a photo to visit our website.

